



DATA SHEET

Toby Aquamax Sports Part A

PRODUCT CODE PART A	701 72420	PART B	701 72424	Data Sheet No. AUDW1314
---------------------	-----------	--------	-----------	-------------------------

APPROVALS	
-----------	--

Features

2 Pack Polyurethane
Waterbased

Benefits

Extremely Hard Wearing
Low Odour, Fast Clean Up

Uses

Performance Guide

Weather Interior use only

Heat Up to 60C

Solvent Good for weak solutions

Acid Good for weak solutions

Salt Good

Water Good for splashes and spillages. Not for
ponding or immersion

Abrasion Good

Alkali Good for weak solutions

Typical Properties and Application Data

Gloss Level 95% min.

Spread Rate 8.8 sqm/L

Components 2.0


Number of Coats 2-3

Mixing Ratio 10:1

Wet film per coat Recommended 114 µm

Dry film per coat Recommended 40 µm

Gloss Level Ind



Volume Solids 27.88

Toxicity Non-toxic.

V.O.C Level < 140g/L

Pot Life 2 hrs

Touch Dry 1-1.5 hrs

Application Method



Data Sheet	Toby Aquamax Sports Part A		
DuSpec Data Code	AUDW1314	Page No	1 of 3
Issue No	3.0	Date Issued	08/07/2007



DATA SHEET

Toby Aquamax Sports Part A

	Data Sheet No.	AUDW1314
--	-----------------------	----------

Application Guide

Surface Preparation

All surfaces must be clean, dry and free from wax, grease, dust and other contaminants. The presence of such contaminants contribute to conditions such as "rejection" or delamination.

Sand the surface with coarse sandpaper initially. All nail holes and crack should be filled with putty, then fine sand the floor, finishing with 100 grit sandpaper. As with other waterbased products, it is advisable to close the grain with a 150-mesh screenback.

Vacuum thoroughly with a commercial grade vacuum cleaner. Use a filter with a minimum screening capacity for capturing dust particles of 1 micron.

It is prudent to measure the moisture level of a floor prior to coating to ensure the timber has stabilised.

Application Procedure and Equipment

Pour premixed Toby Aquamax Sports into a clean, dry plastic pour can.

Pour a 10 cm wide puddle line along one wall, in the same direction as the grain of the wood. Using a T-bar applicator, and holding it at a slight angle, drag it in a "squeegee" or "snow plow" motion. This moves the puddle line towards the opposite wall and maintains a constant wet edge. Keep adding Aquamax Sports to maintain the 10 cm wide puddle line. Reduce the puddle size when approaching the opposite wall. At the end of each row, make a smooth turn with the applicator and squeeze out excess material beside the puddle line and in line with the grain of the timber. Smooth out turn lines along the grain direction. Avoid applicator marks by letting the applicator down gently while in motion.

Allow the coating to dry for approximately 2-4 hours, then lightly sand with a used 150 grit screen. Do not oversand. Vacuum thoroughly and use damp towels to tack the floor to remove residual dust. Repeat the above procedure for the second and third coats of Aquamax Sports.

T-bar Applicator

Notes

MIXING : Toby Aquamax Sports is a two-component product, mixed to the ratio of 10:1 (10 parts Part A to 1 part Part B). Pour Part A through a stocking into the mixing bucket. Use a stirrer attached to a drill at high speed. Add Part B into Part A while mixing and mix for 5 minutes. **DO NOT MIX BY HAND.**

Health and Safety

Health Effects For detailed information refer to the current Material Safety Data Sheet available through Sales and Customer Service offices

Flammability This product is non-flammable

Disposal Do not dispose down the drain. Refer to your local council for correct disposal procedures

In the case of emergency please call 1800 033 111

Precautions and Limitations

Transport and Storage

Pack A 701 72420

Sizes 10L


Weight 12Kg

Pack B 701 72424

Sizes 1L

Weight 1.2Kg

Data Sheet	Toby Aquamax Sports Part A		
DuSpec Data Code	AUDW1314	Page No	2 of 3
Issue No	3.0	Date Issued	08/07/2007



DATA SHEET

Toby Aquamax Sports Part A

Data Sheet No. AUDW1314

Disclaimer

Dulux and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of Orica Consumer Products in relation to goods manufactured by it or their use and application is given in good faith and is believed by Orica Consumer Products to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by Orica Consumer Products is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon Orica Consumer Products by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "Orica" "Dulux" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of Orica Australia Pty Ltd ABN 99 004 117 828. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

Orica Consumer Products 1970 Princes Highway Clayton, Victoria 3168 AU ABN 99 004 117 828

Data Sheet	Toby Aquamax Sports Part A		
DuSpec Data Code	AUDW1314	Page No	3 of 3
Issue No	3.0	Date Issued	08/07/2007