



DATA SHEET

Toby GF Barrier Seal

PRODUCT CODE 70372030

Data Sheet No. AUDW1208

APPROVALS

DESCRIPTION	Toby GF Barrier Seal can be used as a fast drying sealer for strip timber and parquetry. It offers outstanding grain filling properties and excellent barrier properties. The product can reduce the occurrence of rejection on the old timber floors that are recoated with solvent-based Toby timber finishes.
--------------------	--

Features	Benefits
Roller Applied Solvent Based Excellent barrier properties Outsanding grain filling properties	Very easy application Excellent adhesion properties Reduces incidences of "rejection" Reduces surface porosity

Uses
Strip timber and parquetry floors

Performance Guide			
Weather	Interior Only	Salt	NA
Heat	60 C	Water	NA
Solvent	NA	Abrasion	NA
Acid	NA	Alkali	NA

Typical Properties and Application Data			
Gloss Level	0	Thinner	Toby Reducer Thinners
Spread Rate	8.0 sqm/L	Volume Solids	16.0
Components	1.0	Colour	Slightly hazy liquid
Toxicity	Toxic	Number of Coats	1
Shelf life	12 months (in unopened container)	V.O.C Level	High
Sanding Properties	Good	Wet film per coat	Recommended 125 µm
Touch Dry	30 min	Dry film per coat	Recommended 20 µm
Clean Up	Toby Super Solvent	Recoat	1.5 Hrs
		Application Method	



DATA SHEET

Toby GF Barrier Seal

Disclaimer

Data Sheet No. AUDW1208

Dulux and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of Orica Consumer Products in relation to goods manufactured by it or their use and application is given in good faith and is believed by Orica Consumer Products to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by Orica Consumer Products is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon Orica Consumer Products by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "Orica" "Dulux" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of Orica Australia Pty Ltd ABN 99 004 117 828. Marks followed by the symbol ™ are trademarks.

Please note that this specification is only valid for 60 days from the date of issue.

Orica Consumer Products 1970 Princes Highway Clayton, Victoria 3168 AU ABN 99 004 117 828

Data Sheet	Toby GF Barrier Seal		
DuSpec Data Code	AUDW1208	Page No	3 of 3
Issue No	1.0	Date Issued	27/06/2005