



**DATA SHEET**

**Toby Lustapol**

**PRODUCT CODE PART A** 70372201 **PART B** 70372208 **Data Sheet No. AUDW1213**

**APPROVALS**

**DESCRIPTION** Toby Lustapol is a two component solvent based clear polyurethane coating that is a premium, tough, durable chemical and abrasion resistant finish for the protection and enhancement of timber and parquetry floors.

Features	Benefits
2 pack mix Chemical dry	very tough finish More reliable dry in cold conditions

Uses
Timber & parquetry floors

Performance Guide			
<b>Weather</b>	Interior Only	<b>Salt</b>	Excellent
<b>Heat</b>	60 C	<b>Water</b>	Excellent
<b>Solvent</b>	Excellent	<b>Abrasion</b>	Excellent
<b>Acid</b>	Excellent	<b>Alkali</b>	Excellent

Typical Properties and Application Data			
<b>Gloss Level</b>	85-95 at 65 Degrees	<b>Thinner</b>	Toby Reducer Thinners
<b>Gloss Level Ind</b>		<b>Spread Rate</b>	10.2 sqm/L
<b>Volume Solids</b>	46.0	<b>Components</b>	2.0
<b>Colour</b>	Pale straw coloured clear liquid	<b>Toxicity</b>	Toxic
<b>Number of Coats</b>	2	<b>Shelf life</b>	12 months
<b>V.O.C Level</b>	High	<b>Sanding Properties</b>	Good
<b>Mixing Ratio</b>	1:1	<b>Pot Life</b>	4 hrs once mixed
<b>Wet film per coat</b>	Recommended 98 µm	<b>Touch Dry</b>	1-3 hrs
<b>Dry film per coat</b>	Recommended 45 µm	<b>Clean Up</b>	Toby Super Solvent
<b>Recoat</b>	5		
<b>Application Method</b>			



**DATA SHEET**

**Toby Lustapol**

**Application Guide** **Data Sheet No. AUDW1213**

**Surface Preparation**

All surfaces must be clean, dry and free of wax, grease, dust and other contaminants. The presence of such contaminants contributes to conditions such as 'rejection' or 'delamination'.

Sand the surface with coarse sandpaper initially. All nail-holes and cracks should be filled with putty, then fine sand the floor, finishing with 100grit sand paper, then it is advisable to close the grain with a 150-mesh screenback.

Vacuum thoroughly with a commercial grade vacuum cleaner. Use a filter with a minimum screening capacity for capturing dust particles of 1 micron.

**Notes**

**Toby Lustapol is manufactured to the correct consistency for application by mohair roller or soft bristle brush. However, if thickening has occurred due to ageing, thin with up to 10% with Toby Reducer Thinners.**

**SEALER CHOICE**

<b>Timber</b>	<b>Rapid Seal or GF Barrier Seal</b>
<b>Parquet</b>	<b>Rapid Seal or GF Barrier Seal</b>

**Health and Safety**

<b>MSDS Number</b>	20151	<b>Flammability</b>	Flamable
<b>Personal</b>	Do not use if sensitised to isocyanates	<b>Protective Equipment</b>	Full mask with organic vapour cartridge
<b>Storage</b>	Toby Lustapol has a shelf life of at least 12 months, if stored in original, unopened containers, in clean, cool, dry conditions away from sources of heat and naked flames.	<b>Disposal</b>	For large quantities refer to Waste Management Authority. Advise flammable nature. Dispose of material through a licensed waste contractor. Normally suitable for incineration by approved agent. For small quantities: Do not pour leftover material down drain. Unwanted material should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collection. Empty containers should be left open in a well ventilated area to dry out. When dry recycle the container via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may differ between local authorities. Check with your local council first.

**In the case of emergency please call 1800 033 111**

**Precautions and Limitations**

<b>Data Sheet</b>	Toby Lustapol		
<b>DuSpec Data Code</b>	AUDW1213	<b>Page No</b>	2 of 3
<b>Issue No</b>	1.0	<b>Date Issued</b>	27/06/2005



## DATA SHEET

### Toby Lustapol

Transport and Storage		Data Sheet No.	AUDW1213
<b>Pack A</b>	70372201		
<b>Sizes</b>	20 L	<b>Flash point</b>	23 C
<b>Weight</b>	19.4Kg	<b>UN Number</b>	1263
<b>Dangerous Goods Class</b>	flammable	<b>Package Group</b>	3
<b>Shipment Name</b>	Solvent Based		
<b>Pack B</b>	70372208		
<b>Sizes</b>	20L	<b>Flash point</b>	23 C
<b>Weight</b>	20.6Kg	<b>UN Number</b>	1263
<b>Dangerous Goods Class</b>	flammable	<b>Package Group</b>	3

#### Disclaimer

Dulux and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of Orica Consumer Products in relation to goods manufactured by it or their use and application is given in good faith and is believed by Orica Consumer Products to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by Orica Consumer Products is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon Orica Consumer Products by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "Orica" "Dulux" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of Orica Australia Pty Ltd ABN 99 004 117 828. Marks followed by the symbol ™ are trademarks.

Please note that this specification is only valid for 60 days from the date of issue.

Orica Consumer Products 1970 Princes Highway Clayton, Victoria 3168 AU ABN 99 004 117 828

<b>Data Sheet</b>	Toby Lustapol		
<b>DuSpec Data Code</b>	AUDW1213	<b>Page No</b>	3 of 3
<b>Issue No</b>	1.0	<b>Date Issued</b>	27/06/2005