

MATERIAL SAFETY DATA SHEET

1. Identification of Material and Supplier

Product Name

Toby Maxi-1 Sealer

Other Names

n.all.

Recommended Use

Aqueous Urethane/acrylic sealer for timber floors

Supplier Name

Orica Woodcare

ABN 99 004 117 828

Address

1330 Ferntree Gully Rd, SCORESBY VIC 3179

Web Address

www.toby.com.au

Emergency Telephone

1800 033 111(24hrs)

Technical Support

1800073530

2. Hazards Identification

Hazard Classification

This product is non-hazardous according to the criteria of the NOHSC. All components are listed in the AICS. Not classified as DG according to the ADG Code. Not a schedule poison according to the SUSDP.

Risk Phrases

None allocated or required.

Safety Phrases

None allocated or required.

3. Composition/Information on Ingredients

Chemical Identity

All ingredients are determined to be non-hazardous or below cut-off values.

Proportion

100 %

CAS No

n.a.

4. First Aid Measures

4.1 Symptoms of Exposure by Route

SWALLOWED

May cause mild irritation of mouth and throat. May cause feelings of nausea.

EYE

Will cause mild irritation if left in contact. Liquid may cause some transient clouding of the cornea.

SKIN

May cause mild irritation if left in contact.

INHALED

Unlikely to cause problems due to very low vapour pressure. If concentrated, in a small area, may irritate the nose and throat.

4.2 First Aid Instructions

SWALLOWED

Do not induce vomiting. Rinse mouth clear with water and give two 300 ml glasses of water to drink. If symptoms persist seek prompt medical assistance.

EYE

Immediately: Hold eye open and flush with clean water for at least 15 minutes. While flushing, gently pull upper and lower eyelids away from eyes and ensure the inside of the lids are carefully flushed. If symptoms persist seek prompt medical attention.

SKIN

Remove contaminated clothing and footwear (while under safety shower if appropriate). Flush affected area with water for 3-5 minutes followed by washing gently with soap and water for a further 5 minutes. Rinse well and pat dry. If symptoms persist seek prompt medical assistance.

INHALED

Not likely to occur. If patient complains of any symptoms treat symptoms where possible and seek medical advice.

FIRST AID FACILITIES

Provide normal industrial first aid facilities including eye-wash stations and safety showers as appropriate.

Notes to Physician (for symptoms of over-exposure to this product see above)

Possible symptoms of Chronic Health Effects

No records were found linking this product or its ingredients, in the proportion present, to adverse health effects.

Possible aggravated pre-existing conditions

None reported.

Suggested treatment for acute symptoms, known antidotes

Provide supportive care and treatment based on the patient's reactions to the exposure. For further information contact the:

POISONS INFORMATION CENTRE 13 11 26 in all States

5. Fire Fighting Measures

5.1 Flammability and Explosion Hazards

Product is water-based and in most circumstance non-combustible. Steam expansion may rupture containers involved in fire.

5.2 Hazardous Combustion Products

When heated to decomposition as water boils off emits toxic fumes CO_x, NO_x, trace amounts of CN and complex hydrocarbons.

5.3 Suitable Extinguishing Media

Water delivered as fine spray.

Hazchem Code: n.a.

5.4 Precautions for Fire Fighters and Special Equipment

Wear SCBA and full turn out clothing. Avoid bodily contact with substance or run-off. Contain run-off for later collection and controlled disposal.

6. Accidental Release Measures

6.1 Emergency Procedures – Spills and Leaks (See Section 13 for disposal considerations)

Prevent material entering drains. Cover pool with sand, soil or other absorbent. Shovel saturated absorbent into plastic pails or drums. Fit lids, label and place in a safe area to await disposal. Ventilate work area before re-entry if indoors.

7. Handling and Storage

7.1 Handling Advice

Wear suitable protective clothing. Avoid contact with strong oxidisers.

7.2 Storage Advice

Store in a cool, well ventilated area. Keep away from Class 5 goods (Yellow dangerous goods diamonds).

8. Exposure Controls/ Personal Protection

8.1 Exposure Standards

Exposure standards have not been established for the components or for the finished product. In keeping with sound practices keep exposures to the minimum practicable.

Substance

TWA

STEL

8.2 Engineering Control Methods

Provide comfort level ventilation.

8.3 Personal Protective Equipment

Respiratory Protection

Not required.

Eye Protection

Use safety glasses with side shields or goggles to AS 1337

Gloves

Not usually required but if redness or soreness is experienced use rubber or PVA gloves.

Clothing

Wear Tyvec or cotton coveralls fastened at the neck and wrists. Supplement with PVA apron if required.

