

## DATA SHEET

### Toby Rapid Seal

**PRODUCT CODE** 70372949

**Data Sheet No.** AUDW1206






#### APPROVALS

<b>DESCRIPTION</b>	Toby-Rapid seal dries quickly to enable fast recoating and has excellent adhesion to most Australian Timbers. It causes no significant darkening of timbers, and can be recoated with any Toby floor finish.
--------------------	--

Features	Benefits
Roller Applied Solvent Based Special resins	More Productive Excellent adhesion properties Fast dry & re-coat. Will not darken timber

Uses
Interior timber floors

Performance Guide			
<b>Weather</b>	Interior Only	<b>Salt</b>	NA
<b>Heat</b>	NA	<b>Water</b>	NA
<b>Solvent</b>	NA	<b>Abrasion</b>	NA
<b>Acid</b>	NA	<b>Alkali</b>	NA

Typical Properties and Application Data			
<b>Gloss Level</b>	0	<b>Thinner</b>	Toby Reducer Thinners
<b>Spread Rate</b>	9.3 sqm/L	<b>Volume Solids</b>	14.0
<b>Components</b>	1.0	<b>Colour</b>	Milkish White Liquid
<b>Toxicity</b>	Toxic	<b>Shelf life</b>	12 months (in unopened container)
<b>V.O.C Level</b>	High	<b>Sanding Properties</b>	Good
<b>Wet film per coat</b>	Recommended 107 µm	<b>Touch Dry</b>	15 min
<b>Dry film per coat</b>	Recommended 15 µm	<b>Clean Up</b>	Toby Super Solvent
<b>Recoat</b>	7		
<b>Application Method</b>	    		

Application Guide
<p><b>Surface Preparation</b></p> <p>All surfaces must be clean, dry and free of wax, dust and other contaminants. The floor should be sanded with coarse sandpaper. All nail holes and cracks should be filled with putty. Fine sand the floor with 100 or 120-grit sandpaper and close the grain with a 150 mesh screenback.</p>



## DATA SHEET

### Toby Rapid Seal

Health and Safety		Data Sheet No. AUDW1206
<b>MSDS Number</b>	20161	<b>Using Safety Precautions</b> This material is FLAMMABLE. Do not use in the presence of naked flame or electrical appliances, and do not smoke while using. Provide adequate ventilation during application or wear suitable respiratory equipment. Avoid breathing the vapour as it may cause an asthma-like reaction. Repeated over exposure may cause sensitisation. Avoid contact with skin and eyes. Wear eye protection and solvent-resistant gloves when mixing or using this material.  <b>Protective Equipment Disposal</b> Us emask with organic vapour cartridge  For large quantities refer to Waste Management Authority. Advise flammable nature. Dispose of material through a licensed waste contractor. Normally suitable for incineration by approved agent. For small quantities: Do not pour leftover material down drain. Unwanted material should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collection. Empty containers should be left open in a well ventilated area to dry out. When dry recycle the container via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may differ between local authorities. Check with your local council first.
<b>Flammability</b>	Yes	
<b>Storage</b>	Protect from extremes of temperature and frost, store between 5 - 30 C	

**In the case of emergency please call 1800 033 111**

### Precautions and Limitations

### Transport and Storage

<b>Pack A</b>	70372949				
<b>Sizes</b>	4L    20L	<b>Flash point</b>	-7 C	<b>UN Number</b>	1263
<b>Weight</b>	4.1Kg    19.8Kg	<b>Package Group</b>	III	<b>Dangerous Goods Class</b>	Flammable
<b>Dangerous Goods Class</b>	Flammable	<b>Shipment Name</b>	Solvent Based	<b>Flash point</b>	-7 C

<b>Data Sheet</b>	Toby Rapid Seal		
<b>DuSpec Data Code</b>	AUDW1206	<b>Page No</b>	2 of 3
<b>Issue No</b>	1.0	<b>Date Issued</b>	27/06/2005



## DATA SHEET

### Toby Rapid Seal

Disclaimer

Data Sheet No. AUDW1206

Dulux and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of Orica Consumer Products in relation to goods manufactured by it or their use and application is given in good faith and is believed by Orica Consumer Products to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by Orica Consumer Products is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon Orica Consumer Products by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "Orica" "Dulux" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of Orica Australia Pty Ltd ABN 99 004 117 828. Marks followed by the symbol ™ are trademarks.

Please note that this specification is only valid for 60 days from the date of issue.

Orica Consumer Products 1970 Princes Highway Clayton, Victoria 3168 AU ABN 99 004 117 828

Data Sheet	Toby Rapid Seal		
DuSpec Data Code	AUDW1206	Page No	3 of 3
Issue No	1.0	Date Issued	27/06/2005