

# Toby Aquamax Roller Seal



## Roller-applied, water-based sealer

### Description

Toby Aquamax Roller Seal is an environmentally safe, water-based sealer for timber. It seals all timber surfaces and provides a perfectly prepared surface for the application of all Toby Aquamax timber floor finishes. Toby Aquamax Roller Seal can be applied by roller and it reduces the occurrence of shadow marks on the timber floors that are normally a problem with water-based timber floor coatings.

### Special features

- Roller applied
- Fast drying and re-coat time
- Excellent adhesion to all common Australian timbers
- Very user friendly
- Reduces lab and shadow marks

### Properties

<b>Appearance:</b>	Milky white liquid
<b>Viscosity:</b>	15 seconds (ford #4 cup)
<b>Density:</b>	1.04 g/ml
<b>Solids content:</b>	31%
<b>Flammability:</b>	non-flammable
<b>Packaging:</b>	5 litre container
<b>Shelf life:</b>	12 months in unopened container (store between 5 - 30°C)

### Directions for use or Application

#### Surface preparation

All surfaces must be clean, dry, free of wax, grease, dust and other contaminants. The floor should be sanded with coarse sandpaper. All nail holes and cracks should be filled with putty. Fine sand the floor with 100 or 120-grit sandpaper and close the grain with a 150 mesh screenback.

### Typical properties and application data

<b>Application:</b>	9 mm Rolana roller or applicator bar
<b>Coverage:</b>	10 m <sup>2</sup> /litre

### Drying times @ 25°C and 50% RH:

- **Tack free:** 30 - 45 minutes
- **Overcoat time:** 60 - 90 minutes (depending on climatic conditions)

**Note:** Drying times will be subject to climatic conditions, film thickness and air flow.

**Clean up:** Water

**Storage:** Protect from extremes of temperature and frost, store between 5°C and 30°C

### Application technique

Use a paint pad or polyester brush for the edges. Edge out 15 cm from the baseboard and keep a wet edge at all times. Apply product with 9 mm-nap roller finishing in the direction of the boards. Allow approximately 60 – 90 minutes to dry and sand with a worn 150 screen. The product does not need to be sanded in order to achieve adhesion to the next coat, however, we recommend sanding because of the better finish that can be achieved.

Toby Aquamax Roller Seal can be top-coated with Toby Aquamax Domestic or Toby Aquamax Commercial finishes. It may also be used with Toby Aquamax Sport but we recommend a test area as colour bleeding on certain rare timber species may occur.

### Precautions

#### Health and safety

Irritating to eyes and may irritate skin. Potentially harmful if swallowed. Inhaling vapour may cause headache, dizziness and nausea. Avoid direct contact with skin.

#### First Aid

If poisoning occurs, contact a Poisons Information Centre – phone 13 11 26. If swallowed, DO NOT induce vomiting – give a glass of water. If in eyes, hold eyes open, flood with water for at least 15 minutes and see a doctor. If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water.

Material Safety Data Sheets (MSDS) are available to users on request to your nearest Orica Woodcare office or Toby Distributor. Read MSDS, data sheet and label carefully before first use of any product. Orica Woodcare are continually updating materials and methods, so please ensure you have the latest information.

