



DATA SHEET

Toby Solarthane-Plus

PRODUCT CODE 70372024

Data Sheet No. AUDW1207

APPROVALS

DESCRIPTION Toby Solarthane-Plus Sealer has been specifically developed to reduce colouring of timber, particularly darker timbers such as Jarrah.

Features	Benefits
Roller Applied Solvent Based Low gluing characteristics Higher solids Clear resin	More Productive Excellent adhesion properties Helps reduce edgebonding Good grain-filling properties Minimal darkening of floors

Uses
Interior cork and timber floors

Performance Guide			
Weather	Interior Only	Salt	NA
Heat	up to 60C	Water	NA
Solvent	NA	Abrasion	NA
Acid	NA	Alkali	NA

Typical Properties and Application Data			
Gloss Level	0	Thinner	Toby Reducer Thinners
Spread Rate	10.0 sqm/L	Volume Solids	20.0
Components	1.0	Colour	Milkish White Liquid
Toxicity	Toxic	Number of Coats	1
Shelf life	12 months (in unopened container)	V.O.C Level	High
Sanding Properties	Good	Wet film per coat	Recommended 100 µm
Touch Dry	20-30 min	Dry film per coat	Recommended 20 µm
Clean Up	Toby Super Solvent	Recoat	7
	Application Method		



DATA SHEET

Toby Solarthane-Plus

Application Guide	Data Sheet No. AUDW1207
--------------------------	--------------------------------

Surface Preparation

All surfaces must be clean, dry and free of wax, dust and other contaminants. The floor should be sanded with coarse sandpaper. All nail holes and cracks should be filled with putty. Fine sand the floor with 100 or 120-grit sandpaper and close the grain with a 150 mesh screenback. It is advisable to use tack cloths dampened with Toby Thinners to mop the floor. Ensure floor is completely dry before coating.

Toby Solarthane-Plus Sealer is NOT designed for application onto previously coated surfaces.

Health and Safety

MSDS Number	20159	Using Safety Precautions	This material is FLAMMABLE . Do not use in the presence of naked flame or electrical appliances, and do not smoke while using. Provide adequate ventilation during application or wear suitable respiratory equipment. Avoid breathing the vapour as it may cause an asthma-like reaction. Repeated over exposure may cause sensitisation. Avoid contact with skin and eyes. Wear eye protection and solvent-resistant gloves when mixing or using this material.
Flammability	Yes	Protective Equipment	Mask with organic vapour cartridge
Storage	Protect from extremes of temperature and frost, store between 12 - 30 C	Disposal	For large quantities refer to Waste Management Authority. Advise flammable nature. Dispose of material through a licensed waste contractor. Normally suitable for incineration by approved agent. For small quantities: Do not pour leftover material down drain. Unwanted material should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collection. Empty containers should be left open in a well ventilated area to dry out. When dry recycle the container via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may differ between local authorities. Check with your local council first.

In the case of emergency please call 1800 033 111

Precautions and Limitations

Transport and Storage

Pack A	70372024	Flash point	4 C
Sizes	4L 20Kg	UN Number	1263
Weight	4.3Kg 20.6Kg	Shipment Name	Solvent Based
Dangerous Goods Class	Flammable		

Data Sheet	Toby Solarthane-Plus		
DuSpec Data Code	AUDW1207	Page No	2 of 3
Issue No	1.0	Date Issued	27/06/2005



DATA SHEET

Toby Solarthane-Plus

Disclaimer

Data Sheet No. AUDW1207

Dulux and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of Orica Consumer Products in relation to goods manufactured by it or their use and application is given in good faith and is believed by Orica Consumer Products to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by Orica Consumer Products is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon Orica Consumer Products by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "Orica" "Dulux" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of Orica Australia Pty Ltd ABN 99 004 117 828. Marks followed by the symbol ™ are trademarks.

Please note that this specification is only valid for 60 days from the date of issue.

Orica Consumer Products 1970 Princes Highway Clayton, Victoria 3168 AU ABN 99 004 117 828

Data Sheet	Toby Solarthane-Plus		
DuSpec Data Code	AUDW1207	Page No	3 of 3
Issue No	1.0	Date Issued	27/06/2005