

Toby Wet Edge Extender



Solvent Evaporation Inhibitor

Description

Toby Wet Edge Extender is a solvent additive that slows solvent evaporation and increases application working time of Toby Solvent Based Polyurethane Cork and Timber Finishes.

Toby Wet Edge Extender also slows the thickening of Toby Finishes on application equipment in hot weather.

Recommended Uses

Toby Wet Edge Extender should be used where conditions which require the timber coating's wet edge time and application time to be extended. This is often the case in hot weather, especially with faster evaporation products such as Toby Unithane Satin and Matt.

Application

Toby Wet Edge Extender is supplied in ready-to-use form. Typical recommended mix is 1 part Toby Wet Edge Extender to 20 parts of coating ie: 50 ml/litre. This ratio will provide for noticeable effect.

Note: Curing time of Toby Polyurethane Cork and Timber Finishes is not significantly affected by the application of Toby Wet Edge Extender.

Important Note: Do not use both Toby Wet Edge Extender and Toby Flo-add in conjunction with Toby Unithane Satin and Matt Polyurethane Cork and Timber Finishes.

Health and Safety

For detailed information, refer to the current Material Safety Data Sheet available from your local Orica Woodcare sales office.

This material is **flammable**. Do not use in the presence of naked flame. Do not smoke. Provide adequate ventilation during application and avoid breathing vapour. In case of insufficient ventilation, wear suitable respiratory equipment. Breathing the vapour is harmful and may cause an asthma like reaction. Repeated over exposure may cause sensitisation. Keep out of reach of children. Avoid contact with skin and eyes. Wear eye protection and solvent resistant gloves when mixing or using this material.

First Aid Instructions

If poisoning occurs contact a doctor or Poisons Information Centre. If swallowed do NOT induce vomiting. Give a glass of water and seek urgent medical advice. If skin contact occurs remove contaminated clothing and wash skin thoroughly. If in contact with eyes, hold eye open and flood eye with water for 15 minutes and seek medical advice. If excessive inhalation occurs, remove from contaminated area.

Typical Properties and Application Data

Appearance:	Clear liquid
Rec. Max. Dosage:	1 part per 20 parts ie: 50 ml per litre of Timber Finish.
Solvents:	Glycol Ethers
Density:	0.97 g/ml
Solubility in water:	Not soluble
Storage:	Protect from extremes of temperature. Store below 30°C.
Packaging:	1 Litre can
Flammable Liquid	
UN No:	1172
Hazchem:	2[S]
PG:	III

Manufacturer's Comment

Toby Wet Edge Extender has been designed for use only with Toby one pack and two pack Polyurethane Timber Finishes/Coatings, as part of a totally integrated application system. Use with any other manufacturer's product could result in detrimental effects on the product's performance for which Orica Woodcare holds no responsibility, and Orica Woodcare cannot be held responsible for failure to follow application instructions.

Orica Woodcare is continually updating materials and methods. Ensure you have the latest information.

Toby Wet Edge Extender



Orica Woodcare
ABN: 99 004 117 828
1330 Ferntree Gully Rd
SCORESBY VIC 3179

Email: toby_enquiries@orica.com
Internet: www.toby.com.au

7 days a week
Technical Support Hotline : 1800 073 530 Emergency Response: 1800 033 111 (24hrs)

Important note

Orica Woodcare products are guaranteed against defective materials and manufacture and are sold subject to its standard terms and conditions of sale, copies of which may be obtained on request. Whilst the company endeavours to ensure that any advice, recommendation, specification or information it may give is accurate and correct, it cannot, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products, whether or not in accordance with any advice, specification, recommendation or information given by it.

AUS/0138/97/A