

Toby Flo-add



Anti-Rejection Additive for Toby Solvent-Borne Polyurethane Timber Floor Coatings Finishes

Description

Toby Flo-add is a surface tension modifier that enhances contaminant lifting and coatibility of Toby Solvent-Borne Polyurethane Timber Floor Coatings to rejecting surfaces.

Toby Flo-add is suitable for use with Toby one and two pack Polyurethanes Timber Floor Finishes/Coatings, in gloss, satin and matt variants.

Recommended Uses

Toby Flo-add is used as an additive to Toby Solvent Based Polyurethane Timber Floor Finishes where improved wetability is required on timber surfaces affected by contamination. Toby Flo-add will not influence or affect the tack free or curing properties of the Toby Polyurethane Cork and Timber Finish.

Important Note: Do not use both Toby Flo-add and Toby Wet Edge Extender in conjunction with Toby Unithane Satin and Matt Polyurethane Timber Floor Finishes.

Application

Toby Flo-add is supplied in a ready to use form and can be stirred into the application bucket. If added directly into the container/drum containing the Toby Polyurethane Timber Floor Finishes, allow an adequate head space. Then mix by rolling the container/drum and moving the material within with a side-to-side movement.

Recommended Dosage Rate (Maximum Addition) 1 part Toby Flo-add to 100 parts of Toby Polyurethane Timber Floor Finish.

eg: 10ml Toby Flo-add to 1lt Toby Polyurethane Timber Floor Finish/coating.

200ml Toby Flo-add to 20lt Toby Polyurethane Timber Floor Finish/Coating.

Note: If Toby Flo-add was used in a precoat, then the next coat should also contain Toby Flo-add at the same dosage because of a reduced surface tension of the coating.

Cautions

Overdosing or poor mixing in of Toby Toby Flo-add can produce orange peel and adversely effect intercoat adhesion. The 1% dosage is maximum recommended. It is advised to evaluate lower levels wherever possible.

Safety Directions

For detailed information, refer to the current Material Safety Data Sheet available from your local Orica Woodcare sales office.

Flammable. Keep away from sources of ignition. No smoking. Do not empty into drains. Avoid contact with skin, eyes and avoid breathing vapour. Wear eye protection and solvent resistant gloves when mixing or using this material.

First Aid instructions

If poisoning occurs contact a doctor or Poisons Information Centre. If swallowed do NOT induce vomiting. Give a glass of water and seek urgent medical advice. If skin contact occurs remove contaminated clothing and wash skin thoroughly. If in contact with eyes, hold eye open and flood with water for at least 15 minutes and see a doctor. If excessive inhalation occurs, remove from contaminated area.

Follow all warnings and directions fully and carefully.

Manufacturers Comment

Toby Flo-add has been designed for use only with Toby one pack and two pack solvent-borne Polyurethane Timber Finishes, as part of a totally integrated application system. Use with other manufacturer's product could result in detrimental effects on the products' performance.

Typical Properties and Application Data

Appearance:	Clear liquid
Recommended Dosage:	
(Maximum Addition):	1 part per 100 parts Toby Polyurethane Floor Finish
Solids:	5%
Density:	0.75g/ml
Solubility in water:	Not soluble
Storage:	Keep away from ignition sources. Protect from extremes of temperature. Store between 5°C and 30°C.
Packaging:	1 Litre container
UN No:	1992
Hazchem:	3[Y]
P.G:	III

Toby Flo-add



Manufacturer's Comment

Toby Unithane Clear Gloss has been designed for use with Toby Solarthane and Toby Rapid Seal and Toby Unithane Clear Timber and Cork Finishes (Gloss, Satin and Matt) as part of a totally integrated application system. Use with any other manufacturer's products could result in detrimental effects on the product's performance for which Orica Woodcare holds no responsibility, and Orica Woodcare cannot be held responsible for failure to follow application instructions.

Orica Woodcare
ABN: 99 004 117 828
1330 Ferntree Gully Rd
SCORESBY VIC 3179

Email: toby_enquiries@orica.com
Internet: www.toby.com.au

7 days a week
Technical Support Hotline : 1800 073 530 Emergency Response: 1800 033 111(24hrs)

Important note

Orica Woodcare products are guaranteed against defective materials and manufacture and are sold subject to its standard terms and conditions of sale, copies of which may be obtained on request. Whilst the company endeavours to ensure that any advice, recommendation, specification or information it may give is accurate and correct, it cannot, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products, whether or not in accordance with any advice, specification, recommendation or information given by it.